

# NARROW RIM EXIT DEVICES



S988

## 24 - Series - Non Handed

### FL24 - Fire Exit Series - Non Handed

**DOORS** - For all types of single and double doors with a mullion. For mullions, see page 18. Available for 1-3/4" to 2-1/4" thick, up to 4'-0" wide opening. For thicker door, consult factory. Furnished standard for 1-3/4" thick, 3'-0" wide opening.

**FUNCTIONS** - A Universal Exit Device. Add Trim for desired function.

**BASE MATERIAL** - The Cover, Touchbar, Device Channel, Lock/Hinge Side Filler and End Cap are furnished of heavy wrought Brass, Bronze or Stainless Steel. US28 Devices are furnished with Aluminum, Brass, Bronze and Stainless Steel components. See "Base Material and Finish Chart" on page 3.

**CHASSIS** - Investment Cast Steel, Zinc Dichromated.

**LATCHBOLT** - Stainless Steel, Deadlocking, 3/4" throw.

**STRIKES** - No. S988, Black Powder Coated Stainless Steel Roller Strike. For optional strikes see page 30.

**DOGGING** - 1/4 turn hex key dogging standard. NOT available on Fire Exit Hardware.

**TOUCHBAR HEIGHT** - 39-15/16" from floor standard. May be varied as situation dictates.

**U.L. LISTED** - Panic and Fire Exit Hardware. For FIRE EXIT HARDWARE Ratings see page 35. Conforms to UL10C and UBC 7-2.

**ANSI/BHMA** - Devices are BHMA certified for ANSI 156.3, Grade 1.

**FINISHES** - US3, US4, US10, US10B, US26, US26D, US28, US32D. For Finish description see page 3.

**CYLINDERS** - Rim Type for "03" function, Mortise Type for "08" function. Use 1-1/4" long standard mortise cylinder. Cylinders are not furnished standard. Specify when required. For cylinder details see page 19.

**STILE WIDTH** - See Stile Information on page 33.

#### DEVICE OPTIONS

Prefix	Description	page
TS	Touchbar Monitoring Switch .....	29
DTS	Touchbar Monitoring Double Switch .....	29
ELR	Electric Latch Retraction .....	20
DE	Delayed Egress .....	24

To specify add Prefix to Device No. (e.g. TS24)

Suffix	Description	page
CD	Cylinder Dogging .....	19
ALK	Exit Alarm: battery operated .....	27
ALW	Exit Alarm: remote power .....	27
DS	Door Position Monitoring Switch .....	29
SNB	Sex Nut and Bolt .....	3
SEC	Security Screws .....	3
BRL	Braille Touchbar .....	31

To specify add Suffix to Device No. (e.g. 24CD)

# TRIMS

**2900A**  
"A" Lever



**2900B**  
"B" Lever



**2900C**  
"C" Lever



**2900D**  
"D" Lever



**2000C**  
"C" Grip



1. All the escutcheons and levers are castings or forgings.
2. For Lever Trim specify Lever Design (A, B, C, D) and Handing ("A" Lever x RHRB furnished standard).
3. For 2900 Series Trim, US26D finish is furnished for US28 and US32D Devices.
4. 2000 Series Trim is furnished with a wrought plate and extruded solid "C" Grip.

- For Trim dimensions see page 34.
- Trims are BHMA certified for ANSI 156.3, Grade 1.
- Trims are through bolted.
- Cylinder, not furnished standard - Rim type for "03" function, 1-1/4" long mortise type for "08" function.  
For cylinder details see page 19.

ANSI Function	01 Exit Only (cover plate)	02 Dummy Trim	03 Key Retracts Latchbolt	08 Key Locks/Unlocks Lever	14 No Cylinder Lever Always Active
Device Nos.	24 FL24	24 FL24	24 FL24	24 FL24	24 FL24
Trim Nos.	2901 2001	2902A 2002C	2903A 2003C	2908A	2914A

## Device with Trim:

Device No.

Add **Prefix** for options,  
see page 10.

Add **Suffix** for options, see page 10.

Add **Suffix**:

Lever Design (A,B,C,D)  
Grip Design (C)

Add **Suffix**: "KNR" Knurled Lever

**TS24CD x 2908AKNR x RHRB x US26D x S988 x 3'0"x7'0"x1-3/4"**

Device w/options      Trim No.      Hand      Finish      Strike      Door Size

**Device Only:** Device no., hand, finish, strike, and door size including thickness:  
(e.g. TS24CD x RHRB x US26D x S988 x 3'0"x7'0"x1-3/4")

**Trim Only:** Trim no., hand, finish, and door thickness: (e.g. 2908A x RHRB x US26D x 1-3/4")