

WOOD DOOR CONCEALED VERTICAL ROD EXIT DEVICES

S519

2700 - Series - Reversible FL2700 - Fire Exit Series - Reversible

DOORS - For all types of single and double door applications. Available for 1-3/4" to 2-1/4" thick, up to 4'-0" wide by 10'-0" high openings. For thicker doors consult factory. Furnished standard for 1-3/4" thick, 3'-0" wide by 6'-8" to 8'-0" high openings.

FUNCTIONS - Functions are field selectable. The device is furnished for a desired function if specified. If not specified the "03" function is furnished standard.

BASE MATERIAL - The Cover, Touchbar, Device Channel, Lock/Hinge Side Filler and End Cap are furnished of heavy wrought Brass, Bronze or Stainless Steel. US28 Devices are furnished with Aluminum, Brass, Bronze and Stainless Steel components. See "Base Material and Finish Chart" on page 3.

CHASSIS - Lock Stile Assembly - Investment Cast Steel, Zinc Dichromated.

REVERSIBLE - Reversible for all functions and trims. Standard packaging RHRB.

U.L. LISTED - Panic and Fire Exit Hardware. For FIRE EXIT HARDWARE Ratings see page 35. Conforms to UL10C and UBC 7-2.

ANSI/BHMA - Devices are BHMA certified for ANSI 156.3, Grade 1.

FINISHES - US3, US4, US10, US10B, US26, US26D, US28, US32D. For Finish description see page 3.

CYLINDERS - Rim Type, not furnished standard. Specify when required. For cylinder details see page 19.

STILE WIDTH - See Stile Information on page 32.

LESS BOTTOM ROD (LBR) OPTION - Specify suffix "LBR" (e.g. 2708LBR). See U.L. FIRE LABEL RATING Chart on page 35.



VERTICAL RODS - Steel, plated. Top Rod is adjustable from 6'-8" to 8'-0" or from 8'-1" to 10'-0". Additional adjustments are available through the lock front filler.

TOP LATCHBOLT - Stainless Steel, Deadlocking, 3/4" throw.

BOTTOM BOLT - Steel plated, independent action 5/8" throw, with adjustment range to suit 3/4" door undercut.

TOP STRIKE - No. S519 Surface applied, Investment Cast Stainless Steel, Black Powder Coated.

BOTTOM STRIKE - No. S460 Flush mounted, Steel, Black Powder Coated.

DOGGING - 1/4 turn hex key dogging standard. NOT available on Fire Exit Hardware.

TOUCHBAR HEIGHT - 39-15/16" from floor standard. Specify required height if other than standard.

DEVICE OPTIONS

Prefix Description	page
TS Touchbar Monitoring Switch	29
TDS Touchbar Monitoring Double Switch	29
LS Latchbolt Monitoring Switch	29
ELR Electric Latch Retraction	20
DE Delayed Egress	24

To specify add Prefix to Device No. (e.g. TS2703)

Suffix Description	page
CD Cylinder Dogging	19
ALK Exit Alarm: battery operated	27
ALW Exit Alarm: remote power	27
DS Door Position Monitoring Switch	29
LBR Less Bottom Rod	14
SNB Sex Nut and Bolt	3
SEC Security Screws	3
BRL Braille Touchbar	31

To specify add Suffix to Device No. (e.g. 2703CD)

S460

TRIMS

1700A

"A" Grip



1700B

"B" Grip



1700C

"C" Grip



2000C

"C" Grip



1. All Trims are furnished with wrought plates and extruded or cast solid grips.
2. Specify Grip Design (A,B,C) ("A" Grip furnished standard for 1700 Series Trim, "C" Grip furnished standard for 2000 Series Trim)
3. US32D Trim is furnished for US26D and US28 Devices.

3900A

"A" Lever



3900B

"B" Lever



3900C

"C" Lever



3900D

"D" Lever



3900K

"K" Knob



V3908A

Vandal Resistant Trim

A heavy duty lever trim designed to withstand abuse and vandalism. Composed of extra strength shock-absorbing "overload" springs and heavy duty investment cast stainless steel internal components. Lever returns to the "home" position eliminating the need to reset the lever.

1. All the escutcheons and levers are castings or forgings.
2. Specify Lever or Knob Design (A,B,C,D,K) and Handing ("A" Lever x RHRB furnished standard).
3. US26D Trim furnished for US28 and US32D Devices.

- For Trim dimensions see page 34.
- Trims are BHMA certified for ANSI 156.3, Grade 1.
- Trims are through bolted.
- Cylinder, Rim Type, not furnished standard. For cylinder details see page 19.

ANSI Function	01 Exit Only (cover plate)	02 Dummy Trim	03 Key Retracts Latchbolt	05 Key Locks/Unlocks Thumbpiece	08 Key Locks/Unlocks Knob/Lever	14 No Cylinder Knob/Lever Always Active	15 No Cylinder Thumbpiece Always Active
Device Nos.	2703 FL2703	2703 FL2703	2703 FL2703	2708 FL2708	2708 FL2708	2708 FL2708	2708 FL2708
Trim Nos.	1701 2001 3901	1702A 2002C 3902A	1703A 2003C 3903A	1705A 2005C	3908A V3908A	3914A	1715A 2015C

Device with Trim:

Device No.

Add Prefix for options, see page 14.

Add Suffix for options, see page 14.

Add Prefix: "V" Vandal Resistant Lever Trim

Add Suffix:
Lever or Knob Design (A,B,C,D,K)
Grip Design (A,B,C)

Add Suffix: "KNR" Knurled Lever or Grip

TS2708CD x V3908AKNR x RHRB x US26D x 3'0"x7'0"x1-3/4"

Device w/options Trim No. Hand Finish Door Size

Device Only: Device no., hand, finish, strike, and door size including thickness:

(e.g. TS2708CD x RHRB x US26D x 3'0"x7'0"x1-3/4")

Trim Only: Trim no., hand, finish, and door thickness: (e.g. V3908A x RHRB x US26D x 1-3/4")